

AMV9 / CFM Chart



		DIP SWITCH SETTINGS							
		8	7	6	5	4	3	2	1
AMV90453BXA		TON							
	1008/600	1.5		✓	✓	✓			
	1008/800	2.0		✓	✓	✓			✓
	1008/1000	2.5		✓	✓	✓		✓	
	1008/1200	3.0		✓	✓	✓		✓	✓
AMV90704CXA		TON							
	1562/800	2.0		✓	✓	✓			✓
	1562/1000	2.5		✓	✓	✓	✓	✓	
	1562/1200	3.0		✓	✓	✓	✓	✓	
	1562/1429	3.5		✓	✓	✓		✓	✓
	1562/1572	4.0		✓	✓	✓	✓	✓	✓
AMV90905DXA		TON							
	1922/990	2.5		✓	✓	✓	✓		✓
	1922/1210	3.0		✓	✓	✓	✓		✓
	1922/1400	3.5		✓	✓	✓		✓	
	1922/1540	4.0		✓	✓	✓	✓	✓	
	1922/1800	5.0		✓	✓	✓		✓	✓
AMV91155DXA		TON							
	1922/1210	3.0		✓	✓	✓	✓		✓
	1922/1400	3.5		✓	✓	✓		✓	
	1922/1540	4.0		✓	✓	✓	✓	✓	
	1922/1800	5.0		✓	✓	✓		✓	✓

NOTE: Heat Settings (Dip #7 & #8) must be adjusted to establish proper temperature rise in the range noted on the furnace name plate.